



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com

Designer's Data Sheet

Part Number/Ordering Information^{1/}

1N _ _ _

Screening^{2/}

_ = Not screened
TX = TX Level
TXV = TXV Level
S = S Level

Package Type

_ = Axial Leaded
SMS = Surface Mount Square Tab

Voltage/Family

6626 = 200V 6630 = 900V
6627 = 400V 6631 = 1000V
6628 = 600V 6631A = 1100V
6629 = 800V 6631B = 1200V

1N6626 – 1N6631

Series

2.3 – 1.8 AMP HYPER FAST RECOVERY RECTIFIER

200 - 1200 VOLTS

30 - 60 nsec

FEATURES:

- Hyper Fast Recovery: 30 - 60 nsec maximum
- PIV up to 1200 Volts
- Low Reverse Leakage Current
- Hermetically Sealed
- Void Free Construction
- For High Efficiency Applications
- Typical Weight: 0.75 g (Axial Leaded); 0.45 g (SMS)
- TX, TXV, and Space Level Screening Available^{2/}
- QPL registered devices per MIL-PRF-19500/590 may be available, contact factory

MAXIMUM RATINGS^{3/}

		SYM	VALUE	UNIT
Peak Repetitive Reverse Voltage and DC Blocking Voltage	1N6626	V _{RRM} V _{RWM} V _R	200	V _{DC}
	1N6627		400	
	1N6628		600	
	1N6629		800	
	1N6630		900	
	1N6631		1000	
	1N6631A		1100	
	1N6631B		1200	
Average Rectified Forward Current ^{4/} (Average current with a half sine wave including reverse voltage amplitude equal to the magnitude of the full rated V _{RWM})	1N6626 - 6628	I _{O1}	2.3	A
	1N6629 - 6631		1.8	
Peak Surge Current (t _p = 8.3 ms Pulse, Half Sine Wave, Superimposed on I _O , T _A = 25°C)	1N6626 - 6630	I _{FSM}	75	A
	1N6631		60	
Storage Temperature		T _{stg}	-65 to +175	°C
Maximum Operating Temperature		T _J	+150	°C
Maximum Thermal Resistance	Junction to Lead, L = 0.375" (Axial Lead)	R _{θJL}	22	°C/W
	Junction to End Tab (Surface Mount)	R _{θJE}	6.5	

NOTES:


1/ For ordering information, price, operating curves, and availability- Contact factory.

2/ Screening based on MIL-PRF-19500. Screening flows available on request.


3/ Unless otherwise specified, all electrical characteristics @ 25°C.

4/ Derate linearly 1.33 percent/°C for T_L > +75°C (Axial Leaded); Derate linearly 2.5 percent/°C for T_{EC} > +110°C (SMS).

Axial Leaded (_)



Square Tab
Surface Mount
(SMS)



NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0179A

DOC


**Solid State Devices, Inc.**

14701 Firestone Blvd * La Mirada, Ca 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

1N6626 – 1N6631


Series

ELECTRICAL CHARACTERISTICS ^{3/}			SYM	MIN	MAX	UNIT
Instantaneous Forward Voltage Drop (T _A = 25°C, 300 μsec Pulse)	1N6626 - 1N6628	I _F = 2 Adc I _F = 4 Adc	V _{F1} V _{F2}	- -	1.35 1.50	V _{DC}
	1N6629 - 1N6630	I _F = 1.4 Adc I _F = 3 Adc	V _{F1} V _{F2}	- -	1.4 1.7	V _{DC}
	1N6631	I _F = 1.4 Adc I _F = 2 Adc	V _{F1} V _{F2}	- -	1.6 1.95	V _{DC}
Breakdown Voltage (I _R = 50 μA dc pulsed)	1N6626 - 1N6631		B _{VR}	110% of Rated	-	-
	1N6631A, 1N6631B			105% of Rated	-	
Reverse Leakage Current (At Rated V _R , 300 μsec pulse minimum)	1N6626 - 1N6630	T _J = 25°C T _J = 150°C	I _{R1} I _{R2}	- -	2.0 500	μA
Reverse Leakage Current (At Rated V _R , 300 μsec pulse minimum)	1N6631	T _J = 25°C T _J = 150°C	I _{R1} I _{R2}	- -	4.0 600	μA
Junction Capacitance (V _R = 10 V _{DC} , T _A = 25°C, f = 1 MHz)			C _J	-	40	pF
Reverse Recovery Time (I _F = 500 mA, I _R = 1 A, I _{RR} = 250 mA)	1N6626 - 1N6628	T _J = 25°C	t _{rr}	-	30	nsec
	1N6629 - 1N6630	T _J = 25°C	t _{rr}	-	50	nsec
	1N6631	T _J = 25°C	t _{rr}	-	60	nsec

Case Outline: (Axial)

DIM	MIN	MAX
A	0.115"	0.137"
B	0.130"	0.300"
C	0.037"	0.042"
D	0.900"	1.300"

Note: Dimensions prior to soldering

Case Outline: (SMS)

DIM	MIN	MAX
A	0.137"	0.148"
B	0.200"	0.225"
C	0.019"	0.028"
D	0.003"	--

Note: Dimensions prior to soldering

NOTES:

1/ For ordering information, price, operating curves, and availability- Contact factory.

2/ Screening based on MIL-PRF-19500. Screening flows available on request.

3/ Unless otherwise specified, all electrical characteristics @ 25°C .4/ Derate linearly 1.33 percent/ $^\circ\text{C}$ for $T_L > +75^\circ\text{C}$ (Axial Leaded); Derate linearly 2.5 percent/ $^\circ\text{C}$ for $T_{EC} > +110^\circ\text{C}$ (SMS).

NOTE: All specifications are subject to change without notification.
 SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0179A**DOC**